

Sewer Repair Permit

City of Hickory Hills - Building Department

8652 W. 95th Street Hickory Hills, IL 60457
 Phone (708) 237-4140 Fax (708) 237-4141 HHBLD1@HickoryHillsil.org
 Office Use Only

Permit #		Approved By	
Date		Fee	\$ 75

Applicant to complete the below:

Owner	Contractor (Company) Name:
Address	Company Contact Name
Phone	Contact's Phone #
R.E. Index	JULIE #

All repairs, excluding rodding, are required to obtain a sewer repair permit prior to commencement of work including excavation. This information is being provided to help guide you through the permit process. These specifications shall apply only to outside sewer repairs made from the main to the structure connection. Permits for emergency work on weekends and holidays shall be applied for on the first normal working day after the repairs were made regardless of whether repairs are completed and the site has been inspected and backfilled. Prior to any excavation, state law requires JULIE to be contacted for underground utility location at 811 or 1-800-892-0123. All JULIE requirements must be followed prior to excavation. Contractors must have a current contractor's license with the City. (See Contractor License Application) Homeowners completing work must complete the required affidavit. (See Homeowners Affidavit Form)

Construction Requirements:

- SDR #26, cast iron or ductile iron pipe is to be used for piping material and riser (if applicable).
- The sewer repair or replacement section shall be installed in a gravel bed not less than 4 inches nor more than 8 inches, with stone ¾" to 1" in size.
- All connections must be water tight by installation of non-shear mission couplings on both ends and /or gasketed joints. Solvent weld (glued) joints are not acceptable.
- Remove all old pipe out of ditch before backfill.
- Rod out sewer to make sure it is working before backfill.
- Once inspected, cover the sewer line with 2 inches of the same material as the bedding stone and backfill.
- Any municipal property (parkway, street, curbs, sidewalk, etc.) damaged during construction shall be restored, inspected and subject to a one-year maintenance period.
- If applicable, clean out installation must be a 6" pipe riser and watertight cleanout cap installed even with grade.

Inspection:

Inspection is required when repair work is complete prior to backfilling. Contact Public Works at (708) 598-7855 for all inspections required for this permit. The contractor shall call for an inspection approximately ½ hour prior to completion of the sewer repair, but no later than 2:30pm. When a sewer repair is completed after 2:30pm, the inspection shall be scheduled for the following morning. (Monday-Friday). Contractors are required to provide temporary protection for the area being repaired.